A. Input Characteristics:
1) Voltage: 200-250VAC
2) Frequency: 50/60 Hz.
3) Line Current: 16A Maximum
4) Load Capacity: 3.68 KVA
5) Overload Protection: (1) 2P/16A UL489 Circuit Breaker
6) Power Cord: NONE
7) Connector: IEC 60320C20
8) Indicator: Power-on, LED
B. Output Characteristics:
1) Voltage: 200-250VAC
2) Current: 16A (Total Combined Load)
3) Outlets: 12X IEC C13
C. Mechanical Characteristics:
1) Material: CRS
2) Finish: Powder Coat, Black, Fine Texture
3) Lettering: Silk-Screen, White/Epoxy
4) Storage Temp.: -(13) - 149F (-25 - 65C)
D. Operating Environment:
1) Temperature: 32 -122F (0 - 50C)
2) Relative Humidity: 0 - 95% (Non-Condensing)
3) Elevation: 0 - 10.000FT (0 - 3000 m)
E. Regulatory Conformance:
1) Safety Agency: UL/cUL, UL60950-1, CE
2) RoHS: Compliant to Directive 2002/95/EC

PDU, 0U, 33T 72A-116BUUENH0O RQ0
INPUT RATING: 200-250,2W+PE, 50/60 HZ, 16A
OUTPUT RATING: 200-250V, 50/60 HZ, 16A
OUTUETilOAMAX
BMNGH QUIT: 16A MM (TOTAL COMBINED LOAD)
I.T.E.
8»4

- «50

i

i L © ©
33 in [838.2 mm]

©

| 1 v

©

o g

l-TECH COMPANY
Industrial Display Solution

THIS DOCUMENT CONTAINS
PROPRIETARY INFORMATION AND IS
COPYRIGHTED. EXCEPTWITHTHE
WRITTEN PERMISSION OF SPECTRUM
CONTROL, INC. OR ITS SUBSIDIARIES,
SUCH INFORMATION SHALL NOT BE
PUBLISHED OR DISCLOSED TO OTHERS,
OR USED FOR ANY PURPOSE AND THIS
DOCUMENT SHALL NOT BE DUPLICATED
IN WHOLE OR IN PART.

DRAWN:
CarrS

TOLERANCES UNLESS
DTHERWISE SPECIFIED:
RACTIONS ±1/64
DECIMAL .XX ± .020
DECIMAL .XXX ±.010
ANGLES ±0'30'

2* ^ THIRD

ANGLE
PROJECTION

DATE
2/22/2008

SHEET:
1 OF1

Spectrum

Management Systems
12X C13, 1 BREAKER, 0U PDU
72A-116BULEN-00
CODE IDENT
MO:

STATE COLLEGE,
PENNSYLVANIA