KCH Series

FULL IP65 TOUCH LCD MONITOR

A full range of solutions for a wide variety of industrial criteria including extreme temperature resistance or sunlight readable

Touch Function	
Waterproof Design	IP65 chassis, IP65 connectors, IP65 power adapter (alternative)
Housing Design	Stainless steel
OSD Controller	Rear side

Model: KCH1500SIP-FPCAP

15" True Flat Touch Industrial Display-Fully Enclosed NEMA 4/IP65, Resolution:1024x768, 400 nits with PCAP touch solution

Waterproof Anti-oil Dustproof Corrosion-proof

Features:

- Fanless design and compact solution
- Fully IP65 compliant 6-sided stainless steel chassis
- Resolution 1024 x 768dpi
- PCAP / 5 wires resistive touch solution
- All IP65 waterproof connectors
- 1 X VGA; 1 x USB or RS232
- VESA mounting

Specifications:

I/O Port					
VGA USB or RS232					
Power					
DC IN 12 V(Default) or DC IN 19~36V					
Touchscreen		**OS Support**			
PCAP/5 wire resistive		Win 7.8.10; Win Embedded 7,8,10, Win pro 7,8,10			
Display					
Size	15" TFT (4:3)				
Resolution	1024 x 768				
Colors	16.2M				
Luminance (cd/m2)	400				
Contrast Ratio	700:1				
View Angle (H/V)	160/160				
Mechanical & Environmental					
Operation Temperature	0 ~ 45°C for PCAP; -20~55°C for RW				
Storage Temperature	-10°C ~ 70°C				
Storage Humidity	10 ~ 90%, non-condensing				
Mount	VESA mounting(100X100mm)				
Dimension (W x H x D mm)&Weight	438.2 x 335 x 63(9kg)				
Optional					
DVI	1				
HDMI	1				
No Touch Screen	1				
AR Glass	1				
Optional High Brightness Panel					
Resolution	1024x768				
Color	16.2M	16.7M	16.7M	16.2M	16.7M
Luminance(cd/m2)	2000	1600	1000	1000	800
Contrast Ratio	700:1	700:1	1700:1	700:1	700:1
Viewing Angle (H/V°)	160/160	160/160	170/170	160/160	160/160

i-Tech Company LLC
TOLL FREE: (888) 483-2418 • EMAIL: info@itechlcd.com • WEB: www.iTechLCD.com